

Linktower T3 is one of the best seller model by Generac® Tower Light, today available in a newly designed version improved with new features and available with 4x400W metal halide or 4x150W LED lamps designed by Generac®. **Linktower T3** is also available in ATEX version.

LINKTOWER T3

LINKTOWER T3

Still on the market from more than 15 years, the Linktower has been redesigned and renamed into **Linktower T3**, equipped today with new special features and increased performances. Available in three different versions: 4x150W LED, 4x400 Metal Halide and also ATEX anti-explosion version (Class II Div. 2).



LOCKABLE DOORS
Now you can open the side panels to access the inner space that can be used as a safe storage for documents and tools.



JOCKEY WHEEL
Thanks to the new added jockey wheel, **Linktower T3** gains more stability and can be moved more easily and quickly.




NEW STABILIZERS
A renewed design allowing more resistance to strain and improved usability thanks to the new added cranks.



GENERAC® BRANDED LED
The 4x150W configuration is equipped with high efficiency LED floodlights designed by Generac® Tower Light.



LINKABLE IN SERIES
Extreme ease of use! Connect the machine to an external power source and just turn on the lamps with the specific buttons. You can also connect up to four **Linktower T3 MH** or five **Linktower T3 LED** models in series by using the electric outlet sockets.



DOUBLE HAND WINCH
A new redesigned manual winch to raise and lower the mast in few seconds.



TECHNICAL DATA		LINKTOWER T3 MH	LINKTOWER T3 LED	LINKTOWER T3 ATEX
Lifting system	-	Manual	Manual	Manual
Min. dim.	mm	1230 x 780 x 2170	1230 x 780 x 2110	1200 x 800 x 2680
Max. dim.	mm	1870 x 1460 x 6700	1870 x 1460 x 6700	1870 x 1472 x 6700
Dry weight	kg	246	248	281
Lamps power	W	4 x 400	4 x 150	4 x 150
Lamps type	-	Metal Halide	LED	LED
Certified illuminated area	m ²	2,100	2,300	2,200
Total lumen	Lm	144,000	76,500	61,000
Mast rotation	°	340	340	340
Certified wind speed resistance	km/h	80	80	80
Inlet plug	-	32 A - 230 V - 50/60 Hz	16 A - 230 V - 50/60 Hz	16 A - 230 V - 50/60 Hz
Outlet socket	-	32 A - 230 V - 50/60 Hz	16 A - 230 V - 50/60 Hz	-
Trailer	-	Hand trolley	Hand trolley	Hand trolley
Anti-explosion certification	-	-	-	Class II Div. 2

GENERAC® | **MOBILE PRODUCTS**

Generac Mobile Products Srl.
Part of Generac Power Systems, Inc.
Via Stazione, 3 bis - 27030 Villanova d'Ardenghi (PV) - Italy
Tel +39 0382 567011 - gmp.srl@generac.com
www.towerlight.com | www.generacmobileproducts.com

